


Enduralux LED


975 LINEAR

LUMINAIRE



IK 10++

IP 54



Introduction

Light Years Ahead Ltd (LYA) is a leading UK manufacturer of anti-ligature, vandal resistant lighting solutions for the custodial, healthcare, civil and industrial sectors.


LYA have established a leading position in the custodial sector

with thousands of luminaires installed in prisons, courts and police stations across the UK and abroad. LYA's Enduralux and Protectalux brands are renowned for their durability and include a range of Ministry of Justice approved products for use in safer and standard cells.

Primary Applications

Custodial	Cells, corridors, communal areas
Healthcare	Patient rooms, hospital wards, corridors
Civil / Industrial	Car parks, railways stations, subways


Product Dimensions



Features & Benefits

- Anti-ligature, vandal resistant luminaire suitable for high risk environments
- High impact resistant (IK 10++) 5mm polycarbonate lens secured by tamper proof TORX security screws
- 1.5mm zintec coated mild steel powder coated (RAL 9003) base plate
- Removable GearTray and LED engine mounting plate
- Tridonic electronic componentry
- Suitable for ceiling or wall mounting
- Conduit entry through centre of base plate
- Dimmable, night-light and integral 3-hour duration emergency battery pack options
- Various colour and light output options
- Fully compliant with BS EN 60598-1


Polar Plot: EN-975-NM-CW



Enduralux LED 975 LINEAR LUMINAIRE

Ordering Guide & Lighting Data

IES / LDT Files available on Request



LIGHTING DATA—5MM CLEAR LENS

Product Code	CRI	Colour (CCT)	Lumens (Lum)	Wattage (W)	Lum / W	Weight (Kg)
EN-975-LO-WW	>80	3000k	2,772	28	98	4.9
EN-975-HE-WW	>80	3000k	3,918	38	102	4.9
EN-975-NM-WW	>80	3000k	5,528	57	98	4.9
EN-975-HO-WW	>80	3000k	7,387	81	92	4.9
EN-975-LO-CW	>80	4000k	2,896	28	102	4.9
EN-975-HE-CW	>80	4000k	4,068	38	106	4.9
EN-975-NM-CW	>80	4000k	5,778	57	102	4.9
EN-975-HO-CW	>80	4000k	7,674	81	95	4.9

Options

- 5mm Opal Lens—add suffix OP
- Night-light—add suffix NL
- Integral 3 hour emergency battery pack—add suffix EP
- DALI — add suffix DA

Installation

- Back plate secured to ceiling or wall via 8mm sleeve anchors
- GearTray and LED mounting plate secured by M4 NYLOC nuts
- Lens secured by M6 TORX security screws (TX30 BO driver)

For additional details on the Enduralux LED product or other lighting products and solutions in the Light Years Ahead portfolio, please do not hesitate to contact our expert team using the contact information below.

