

Enduralux® T Cornice Clear

1250 / 1525 Linear Luminaire

Product Specification



HIGH RISK



MENTAL HEALTH



CUSTODIAL



INFRASTRUCTURE

Features & Benefits

- Anti-vandal luminaire suitable for high-risk environments
- High-impact resistant IK15 (125J) 4mm LED clear polycarbonate lens and opal LED cover for low glare secured by tamper-proof Resistorx security screws
- 1.2mm zinc coated mild steel with powder coated (RAL 9003) base plate
- Removable gear tray and LED engine mounting
- Tridonic electronic replaceable components
- Suitable for cornice or wall mounting
- Conduit entry through centre of back. Optional end entry available
- Dimmable, night light and integral three-hour duration emergency options available, including self-test, EmPro, wireless and Melagen dynamic lighting
- Various colour and light output options
- Fully tested and compliant with BS EN 60598-1



Primary Applications

High Risk

Designed for low, medium and high-risk secure services

Custodial

Corridors, communal area and workshops

Secure Healthcare

Hospital wards and corridors

Infrastructure

Car parks, railway stations and subways

Specification Assist

Linear luminaire, anti-vandal >IK11 (50J) and >IP65 with 1.2mm zinc coated steel body and 4mm polycarbonate clear/frosted lens, secured with Resistorx screws. Part L compliant (>130lm/W), low flicker adjustable LED driver, replaceable LEDs with CRI >80 and lifetime in excess of 72,000 hours

Designed and
Manufactured
in the UK



+44 (0) 1787 881191

info@lightyearsahed.co.uk

lightyearsahed.co.uk

Church Field Road, Sudbury, Suffolk CO10 2YA

**LIGHT
YEARS AHED**

Enduralux® T Cornice Clear

1250 / 1525 Linear Luminaire

Product Dimensions



Lighting Data

Product Code	CRI	Colour Temp	Lumens (lm)	Wattage (w)	lm/W	Weight (kg)
ENTC-1250-MN-4K-CL	>80	4000K	1521	12	127	7.5
ENTC-1250-L0-4K-CL	>80	4000K	2020	15	134	7.5
ENTC-1250-L1-4K-CL	>80	4000K	2514	19	135	7.5
ENTC-1250-L2-4K-CL	>80	4000K	3000	22	138	7.5
ENTC-1250-L3-4K-CL	>80	4000K	3498	25	137	7.5
ENTC-1250-L4-4K-CL	>80	4000K	3968	29	136	7.5
ENTC-1250-L5-4K-CL	>80	4000K	4424	33	134	7.5
ENTC-1250-L6-4K-CL	>80	4000K	4867	36	132	7.5
ENTC-1250-L7-4K-CL	>80	4000K	5255	40	131	7.5
ENTC-1250-L8-4K-CL	>80	4000K	5683	44	129	7.5
ENTC-1250-L9-4K-CL	>80	4000K	6121	48	128	7.5
ENTC-1250-MX-4K-CL	>80	4000K	6564	52	126	7.5

Optional Extras

Additional options are available. Please contact us for more information.

-EP	Integral emergency	-DA	DALI	-PB	RAL9005 black finish
-EPS	Integral self-test emergency	-SD	Switch dim	-PG	RAL7016 grey finish
-EPD	Integral DALI emergency	-MW	Microwave sensor	-3K	3000K (5% lower lumen)
-CB	Central battery inverter	-BT	Bluetooth control		

For additional details on this or any other lighting products and solutions in the Light Years Ahead portfolio, please contact our expert team.

+44 (0) 1787 881191

info@lightyearsahead.co.uk

lightyearsahead.co.uk

Church Field Road, Sudbury, Suffolk CO10 2YA

LIGHT YEARS AHEAD

Light Years Ahead is a company registered in England & Wales. Registration Number: 10722911.

Enduralux® T Cornice Clear

1250 / 1525 Linear Luminaire

Product Dimensions



Lighting Data

Product Code	CRI	Colour Temp	Lumens (lm)	Wattage (w)	lm/W	Weight (kg)
ENTC-1525-MN-4K-CL	>80	4000K	1902	14	136	9.0
ENTC-1525-L0-4K-CL	>80	4000K	2525	19	136	9.0
ENTC-1525-L1-4K-CL	>80	4000K	3142	23	136	9.0
ENTC-1525-L2-4K-CL	>80	4000K	3750	27	138	9.0
ENTC-1525-L3-4K-CL	>80	4000K	4373	32	138	9.0
ENTC-1525-L4-4K-CL	>80	4000K	4960	36	136	9.0
ENTC-1525-L5-4K-CL	>80	4000K	5530	41	135	9.0
ENTC-1525-L6-4K-CL	>80	4000K	6084	46	133	9.0
ENTC-1525-L7-4K-CL	>80	4000K	6570	51	129	9.0
ENTC-1525-L8-4K-CL	>80	4000K	7106	55	129	9.0
ENTC-1525-L9-4K-CL	>80	4000K	7652	60	128	9.0
ENTC-1525-MX-4K-CL	>80	4000K	8206	65	126	9.0

Optional Extras

Additional options are available. Please contact us for more information.

-EP	Integral emergency	-DA	DALI	-PB	RAL9005 black finish
-EPS	Integral self-test emergency	-SD	Switch dim	-PG	RAL7016 grey finish
-EPD	Integral DALI emergency	-MW	Microwave sensor	-3K	3000K (5% lower lumen)
-CB	Central battery inverter	-BT	Bluetooth control		

For additional details on this or any other lighting products and solutions in the Light Years Ahead portfolio, please contact our expert team.

+44 (0) 1787 881191

info@lightyearsahead.co.uk

lightyearsahead.co.uk

Church Field Road, Sudbury, Suffolk CO10 2YA

LIGHT YEARS AHEAD

Light Years Ahead is a company registered in England & Wales. Registration Number: 10722911.