

# Protectalux® XS Cornice

Safer Cell Luminaire

## Product Specification



## Features & Benefits

- Ministry of Justice (MoJ) approved anti-ligature vandal-resistant luminaire suitable for safer cell accommodation
- LED versions on MoJ list of approved products tested in accordance with STD/E/SPEC/022
- Anti-vandal IK20 (250J) 10mm polycarbonate lens secured by tamper-proof Resistox security screws
- 2mm mild steel powder coated lens frame and lid
- Removable gear tray and LED engine plate
- Option for mains lighting on two separate circuits allowing for low, medium and high output levels. Separate night light. Efficacy over 100 lm/W
- Bespoke blank end sections available to provide continuous system including provision for CCTV and smoke detectors

## Primary Applications

### High Risk

Designed for low, medium and high-risk secure services

### Custodial

Prison safer cell accommodation as specified by the Ministry of Justice and police custody suites, court cells and police holding cells

### Mental Health

High risk patient accommodation

### Infrastructure

Car parks, railway stations and subways

## Standard Features

- Mains and night light outputs consistent with MoJ standard cell accommodation specified lux levels
- 3000K colour temperature as specified by the MoJ



Designed and  
Manufactured  
in the UK



+44 (0)1787 881191  
info@lightyearsahead.co.uk

**lightyearsahead.co.uk**


Church Field Road, Sudbury, Suffolk CO10 2YA

**LIGHT YEARS AHEAD**

# Protectalux® XS Cornice

Safer Cell Luminaire

## Product Dimensions



## Lighting Data

Product Code	Length (mm)	CRI	Colour Temp	Lumens (lm)	Wattage (W)	lm/W	Weight (kg)
PRCXS-700-L0-3K	700	>80	3000K	999	9	106	12.5
PRCXS-700-L8-3K	700	>80	3000K	2932	29	100	12.5
PRCXS-1000-L2-3K	1000	>80	3000K	2256	21	106	15
PRCXS-1000-L8-3K	1000	>80	3000K	4398	44	100	15
PRCXS-1300-L2-3K	1300	>80	3000K	3008	28	106	17.5
PRCXS-1300-L8-3K	1300	>80	3000K	5864	58	101	17.5
PRCXS-1600-L2-3K	1600	>80	3000K	3760	35	106	20
PRCXS-1600-L8-3K	1600	>80	3000K	7330	73	100	20

## Optional Extras

Additional options are available. Please contact us for more information.

-EP	Integral emergency	-DA	DALI	-PB	RAL9005 black finish
-EPS	Integral self-test emergency	-NL	Night light	-PG	RAL7016 grey finish
-EPD	Integral DALI emergency	-SW	Switched output	-4K	4000K (5% higher lumen)
-CB	Central battery inverter	-MW	Microwave sensor	-MG	Melagen

For additional details on this or any other lighting products and solutions in the Light Years Ahead portfolio, please contact our expert team.

+44 (0)1787 881191  
info@lightyearshead.co.uk

**lightyearshead.co.uk**

Church Field Road, Sudbury, Suffolk CO10 2YA

**LIGHT YEARS AHEAD**